Heliport Light Controller

AH-HP/G

AH-HP/G Heliport Light Controller use 304 stainless steel material as enclosure with good waterproof, UV protection and surge protection device, so it can be used in very bad environment. It's be used to turn ON and OFF of all Heliport lighting.


Compliance

• ICAO and FAA regulations and CAP437 (offshore helipads)

Features

- Power supply available in 12VDC, 48VDC, 110VAC,240VAC, etc
- Enclosure material is stainless steel 304(stainless steel 316 as optional), good waterproof, UV protection
- Surge protection (anti lightning In 15KA/5, max 40KA)
- Main air switch for over voltage protection
- IP65 Water proof for outside use

SPECIFICATIONS	AH-HP/G Heliport Light Controller
Electrical Characteristics	~~~
Operating Voltage	12VDC, 48VDC, 110VAC, 240VAC, etc
Control Capacity	Customized
Physical Characteristics	
Body Material	Stainless steel 304(SS316, Metal is optional)
Overall size(mm)	$480 \times 300 \times 172$ (Standard, others optional)
Installation size(mm)	$440 \times 260 \times 010$ (Standard, others optional)
Weight(kg)	7.5 (Standard, others optional)
Product Life Expectancy	Average 5 years
Environmental Factors	
Ambient Temperature(℃)	-55~70
Humidity	0~95%
Wind Speed	80m/s
Waterproof	IP65
Options Available	
	Air-To-Ground Radio Control(VHF)
	Adjust light intensity(25%, 50%, 100%),
	Wireless Remote Control




ANHANG TECHNOLOGY

Tel/Fax: +86-755-89589401 Email: <u>sales@annhung.com</u> Website: <u>www.annhung.com</u>

DOC: DT2018AHHPGHPL © Anhang Technology 2016 | All rights reserved

Dimension(mm)





\NNHUNG

守航科技



IP65



X

